



## SLEEPERLAYER SL800 HD

Designed for high output sleeper laying

Up to eight adjacent sleepers can be laid simultaneously from an accompanying supply. Lifted into position, their correct placement is ensured by a precision gauging system that spreads the sleepers to the desired distance.

The telescopic frame structure make it small and safe to operate

No risk of pointing out on the adjacent track when grabbing sleepers from a rail car

As an option the unit can be equipped with a safety lifting device to prevent the operator from dropping sleepers.

Easy adjustable, fit most type of sleepers.

NETWORK RAIL PRODUCT ACCEPTANCE NO; PA05/03134

### SPECIFICATIONS

|                          |                                      |
|--------------------------|--------------------------------------|
| WEIGHT                   | 2410 kg (5313 lb)                    |
| WIDTH                    | 2578 mm (101.5 in)                   |
| LENGTH (min-max)         | 3005 - 5985 mm<br>(118.3 - 235.6 in) |
| HEIGHT (without bracket) | 1660 mm (65.4 in)                    |

*Please note that the unit pictured could be equipped beyond standard. The company reserves the right to make changes without prior notice.*

# ROSENQVIST

Rosenqvist Rail AB, Box 334, S-824 27 HUDIKSVALL, SWEDEN  
Phone +46 650-165 05 Fax +46 650-165 01  
[www.rosenqvistrail.se](http://www.rosenqvistrail.se)